



KRAMER

WP-5VH2

Active Wall Plate – 4K UHD HDMI & Computer Graphics with Ethernet, Bidirectional RS-232 & Stereo Audio HDBaseT Transmitter



The WP-5VH2 4K UHD HDBaseT active wall plate auto switcher is the first of its kind to offer [\[email protected\]](#) UHD (4:2:0) resolution with EDID management, HDMI, VGA, analog audio, and HDMI audio embedding and de-embedding.

This product offers the versatility of a fully-featured auto-switcher with the convenience and simplicity of a wall plate. The WP-5VH2 is easy to configure, can be powered remotely over Ethernet (PoE) and is designed for any size room.

FEATURES

- Resolution Support - Up to [\[email protected\]](#) UHD (4:2:0).
- Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant - Works with sources that support HDCP repeater mode.
- HDMI Support - Deep Color, x.v.Color™ and 3D.
- Automatic Live Input Detection - Based on video clock presence.
- Automatic Input Selection - Based on manual selection or last connected input.
- Automatic Analog Audio Detection & Embedding.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- Range - Up to 130m (430ft) at normal mode (2K), up to 100m at normal mode (4K); up to 180m (590ft) ultra mode (1080p @60Hz @24bpp) when using BC-HDKat6a cables.
- Lockable EDID.
- Flexible Control Options - Via Kramer Protocol 3000 and embedded Web pages over RS-232.
- Digital Audio Format Support.

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI on an HDMI connector, 1 VGA on a 15-pin HD (F) connector, 1 unbalanced stereo audio on a 3.5mm mini jack.
OUTPUTS:	1 HDBaseT on an RJ-45, 1 unbalanced stereo audio on a 3.5mm mini jack.
PORTS:	1 Ethernet on an RJ-45 connector, 1 RS-232 3-pin terminal block.
CONTROLS:	Remote switches for input switching and volume control, reset switch.
STANDARDS:	HDMI with Deep Color, x.v.Color™ and 3D; HDCP works with sources that support HDCP repeater mode; HDBT certified.
MAXIMUM TRANSMISSION DISTANCE:	180m (590ft) up to 1080p @60Hz @24bpp in extended mode, 130m (430ft) up to 1080p @60 @36bpp in normal mode.
POWER CONSUMPTION:	12V DC, 820mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	−40° to +70°C (−40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
COOLING:	Convection, vents.
ENCLOSURE TYPE:	Aluminium.
DIMENSIONS:	11.4cm x 3.8cm x 11.4cm (4.5" x 1.49" x 4.5) W, D, H.
WEIGHT:	0.39kg (0.86lbs) approx.
SHIPPING WEIGHT:	0.68kg (1.5lbs) approx.
VIBRATION:	ISTA 1A in carton (International Safe Transit Association).
REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.
INCLUDED ACCESSORIES:	Power adapter.
WARRANTY:	7 years parts and labor.

CONFIGURATIONS

WP-5VH2-BLNK
WP-5VH2-BLNK

WP-5VH2 Blank Panel - Black
WP-5VH2 Blank Panel - White

