



XE-12S

1:2 s-Video Distribution Amplifier



The XE-12S is a compact, high-performance distribution amplifier for s-Video signals. The unit takes one input and distributes the signal to two identical outputs on 4-pin connectors.

FEATURES

High Bandwidth - 85MHz.

Input - 1 s-Video on a 4-pin connector.

Outputs - 2 s-Video on 4-pin connectors.

Indicator - Power LED.

Accessories - 5V DC power supply, mounting bracket.



XE-12S

TECHNICAL SPECIFICATIONS

INPUT:	1 s-Video on a 4-pin connector.
OUTPUTS:	2 s-Video on 4-pin connectors.
BANDWIDTH (-3dB):	85MHz.
MAX. OUTPUT LEVEL:	3.3Vpp.
DIFF. GAIN:	0.05%.
DIFF. PHASE:	0.05Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	75dB.
COUPLING:	Luma: DC, chroma: AC.
CROSSTALK:	-46dB @5MHz.
INDICATOR:	Power LED.
POWER SOURCE:	5V DC, 47mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 0.98" x 2.95") W, D, H.
WEIGHT:	0.3kg (0.66lbs).
ACCESSORIES:	Power supply, mounting bracket.

