



XE-12X

1:2 Computer Graphics Video Distribution Amplifier



The XE-12X is a compact, high-performance distribution amplifier for computer graphics video signals up to UXGA. The unit takes one input, provides correct buffering and isolation, and distributes the signal to two identical outputs on 15-pin HD connectors.

FEATURES

High Bandwidth - 370MHz.

HDTV Compatible.

Input - 1 computer graphics video with resolutions up to UXGA on a 15-pin HD connector.

Outputs - 2 computer graphics video with resolutions up to UXGA on 15-pin HD connectors.

Indicator - Power LED.

Accessories - 5V DC power supply.



XE-12X

TECHNICAL SPECIFICATIONS

INPUT: 1 computer graphics video with resolutions up to UXGA on a 15-pin HD connector.

OUTPUTS: 2 computer graphics video with resolutions up to UXGA on 15-pin HD connectors.

BANDWIDTH (-3dB): 370MHz.

DIFF. GAIN: 0.03%.

DIFF. PHASE: 0.03Deg.

K-FACTOR: <0.05%.

S/N RATIO: 71dB.

COUPLING: DC.

INDICATOR: Power LED.

POWER SOURCE: 5V DC, 76mA.

DIMENSIONS: 12cm x 7.5cm x 2.5cm (4.7" x 0.98" x 2.95") W, D, H.

WEIGHT: 0.14kg (0.31lbs) approx.

ACCESSORIES: Power supply, mounting bracket.

