

System	RH45D(Head) + RT40RB(Tripod) + BR-6B(Mid-level spreader) + FP-2B(Large rubber feet) + RC-50(Carrying case)		
Payload	12 kg / 26.5 lb	Tilt angle	+90° / -70° (Limited to ±40° with maximum counterbalance)
Weight	6.5 kg / 14.3 lb	Pan angle	360°
Height	① H : 1710 mm W : 880 mm (※Reference)	Counterbalance	Range : 4.5kg-10.5kg / 10-23.1lb (CG100mm)
	② H : 825 mm W : 670 mm (")		System : Continuous
Folded length	③ L : 895 mm (")	Drag mode	Free plus 3STEP
Camera plate (Sliding range)	Sliding plate ±40 mm / ±1.6"	Ball diameter	∅75 mm
Plate attachment (Screw sliding range)	Type: 1/4-20UNC screw with video pin	Tripod fixation	Fixing lock knob
	76 mm / 3"	Spreader	BR-6B (Telescopic, Removable)
Spare screw	Type: 1/4-20UNC , 3/8-16UNC screws	Pan handle	PH-6B
	Equipped on the top of the head (beneath sliding plate)	Case material	Nylon, TPE, PE, PP, POM, ABS

Remarks

※Counterbalance support knob is included in RS-450DM

■Exterior Dimensions (mm)

