

| | | | |
|---|---|----------------|---|
| System | RHP85 (Head) + PH-8B (Pan handle) × 2 + P110S (Pedestal system) | | |
| Payload | 25 kg / 55 lb | Tilt angle | +90° / -70° (Limited to ±40° with maximum counterbalance) |
| Weight | 22.8 kg / 50.2 lb | Pan angle | 360° |
| Height | Max : 1735 mm / 68.5" | Counterbalance | Range : 9~20 kg / 20~44 lb (CG125mm) |
| | Min : 985 mm / 39" | | System : Continuous |
| Camera plate (Sliding range) | 2 Sliding plates (Standard + Long) | Drag mode | 7 STEP |
| | Standard : ±55 mm / ±2.2", Long : ±85 mm / ±3.3" | Ball diameter | φ 100 mm |
| Plate attachment (Screw sliding range) | Type : 3/8-16UNC × 2 | Column | 2 STAGE |
| | Standard : 102 mm / ±4", Long : 95 mm / ±3.7" | | Upper column : air pressure , Mid column : manual |
| Spare screw | Type : 3/8-16UNC × 1 | Pan handle | PH-8B × 2 |
| | Equipped on the head (Behind the platform of sliding plate) | | |

Remarks

■ Exterior Dimensions (mm)

■ RHP85

