


**NEW**



Price: \$1495.00

**V-R682P Dual 6.8" Rack Mounted Full Color Active Matrix LCD Panel with Dual Composite Video inputs and Loop Through feature**

Display (Viewing area)	6.8" (5.44" x 4.07")
Resolution (Pixels)	384 H x 234 V
Dot Pitch	0.120 mm x 0.442 mm
Brightness (in cd/m <sup>2</sup> )	300 cd/m <sup>2</sup>
System	NTSC/PAL auto rec
Inputs per panel (total)	2 Composite with active loop outputs
Dimensions	19.125"W x 5.14"H x 2.5"D
Approx. Weight	5 lbs
Power Consumption	12 VDC, 3.0 Amps



The **V-R682P** is a rack-mounted unit that has two 6.8" active matrix LCD panels with 4:3 aspect ratio. The panels have 384 x 234 dots (RGB pixels) producing a true high-resolution image. There are 2 composite inputs with dedicated A/B switching per display. An active loop through feature is also provided for each input. The unit is designed to fit into an EIA standard 19" rack and occupies 3RU of space. Each screen has a built-in color bar generator. For ease of operation the V-R682P includes dedicated individual front mounted selector buttons with LED indicators plus color, tint, brightness and contrast controls. A U.L. Class 2 power supply and manual are included and the unit is factory ready for rack mount installation.


- High Resolution 384 x 234 Dots , 270,000 total
- Bright 300 cd/m<sup>2</sup> candle luminance
- Automatic NTSC/PAL signal recognition
- Fits in standard 19" rack, 3U high
- Active loop through feature
- Individual color, tint, brightness and contrast controls for each panel
- Built-in Color Bar Generator
- Unique 180 degree tilt adjustment while mounted in rack



Price: \$1999.00

**V-R72DP-2C Dual Screen 1.2 TFT MegaPixel Analog Composite PAL/NTSC Monitor Set**

Display (Viewing area)	7" (6.14" x 3.27")
Resolution (Pixels)	800 H x RGB x 480 V
Dot Pitch	0.105 mm x 0.16 mm
Brightness (in cd/m <sup>2</sup> )	380 cd/m <sup>2</sup>
System	NTSC/PAL auto rec
Inputs per panel (total)	2(4) Composite
Dimensions	19.12"W x 5.14"H x 2.5"D
Approx. Weight	5 lbs
Power Consumption	12 VDC, 3.0 Amps



**1.2 TFT MEGAPIXEL**

The Rack mounted and tiltable **V-R72DP-2C** represents leading edge technology in LCD/TFT imaging for broadcast and professional video applications. The V-R72DP-2C has the highest resolution TFT screens and completely digital signal processing. Analog signals are digitized using an advanced 10 bit process on each signal path with 4x over sampling and adaptive 5 line comb filter with exacting color space conversion. All video formats are scaled to fit on screen in the highest resolution using state of the art LSIs that incorporate 4 x 4 pixel interpolation with precision Gamma correction to produce the best images available.

- High Resolution 7-inch wide screen
- 800 x RGB x 480 Dots with 1.2 million pixels
- 100% digital processing
- Analog signals converted to 10 bit digital
- High resolution scaling of all images
- Wide viewing radius - 130° horizontal and 120° vertical provides superior visibility when the viewer is not directly in front of the screen
- 380 candelas per square meter (cd/m<sup>2</sup>) luminance produces enhanced image quality in varying light and viewing conditions
- 400:1 ratio of contrast between black and white luminance values with response rates less than 30 ms results in excellent quality for moving images
- 4:3 and 16:9 screen aspect ratios for DTV applications
- Automatic NTSC/PAL format detection
- Standard inputs:
  - 2 Composite Video PAL/NTSC per screen
  - Loop through of all inputs signals
- Easy to see three color tally indicators
- Built in Color Bars
- Blue Screen for color adjustment
- Adjustment Settings Memory