## Personal Wireless PA Systems

## **Ultra Portable Model Comparison Chart**

Model	MA-100SB	MA-100DB	MA-101B	MA-202B		
Choose the right MIPRO for you	MiPRO COLOR	MiPRO COLLEGE	MIPRO			
Suggested Usage	School playgrounds, meetings, presentations, mobile announcements, emergencies, tours,		Meetings, presentations, school classrooms & playgrounds, emergencies, tours	Meetings, presentations, schools, seminars		
*Estimated Crowd Size	up to 250		up to 200	up to 300		
Max. Power Output	50 Watts		45 Watts	56 Watts		
Amplifier	Class D		Class AB	Class D		
Sensitivity	Typical: 90 dB Maximum: 102 dB		Typical: 95 dB Maximum: 107 dB	Typical: 96 dB Maximum: 105 dB		
T.H.D.	< 1%					
Speaker	5 " Full-Range	1 " Tweeter 5 " Woofer				
Power Supply	External 100~240V AC switching power supply					
Built-It Battery	Rechargeable Lithium MB-10 x 1		Rechargeable Lithium MB-25 x 1			
Charge Time	Up to 4 hours					
Standby Time	Up to 12 hours	Up to 10 hours	Up to 10 hours	Up to 8 hours		
Battery Indicator	4-level Indicator		Single Indicator	3-level Mic & 4-level Amp Indicators		
Built-in Alarm Tone	Yes		No	No		
Mic Storage in Main Unit	No		No	Yes (ACT-202T)		
Storage Compartment	No		Yes	No		
Line-Input	3.5 mm (1/8 ") x 1			6.3 mm (1/4 ") x 1		
Line-Output	3.5 mm (1/8 ") x 1			No		
Wired Mic-Input	6.3 mm (1/4 ") × 1					
Installation	Shoulder Strap, Hand Carry , Flat Surface or Microphone Stand					
Stand Type	MS-30 Microphone Stand					

Storage Cover	SC-10	SC-20						
Dimensions (W× H× D)	135 × 140 × 240 mm (5.3 × 5.5 × 9.4 ")			60 × 178 × 285 mm 6.3 × 7 × 11.2 ")	163 × 206 × 306 mm (6.4 × 8.1 × 12 ")			
Approx. Weight (battery included)	1.8 kg (3.9 lbs)	1.9 kg (4.1 lbs)	2	2.2 kg (4.8 lbs)	3.1 kg (6.8 lbs)			
Color	Black, optional White		G	Grayish Black	Black			
Wireless System								
Maximum Receiver	1	2		1				
Receiver Installation	Built-in							
Preset Channels	16							
Channel Set-Up	Scan & Sync (ACT)							
Transmitter	Handheld: ACT-32H Bodypack: ACT-32T	Handheld: ACT-222T ACT-32H Bodypack: ACT-32T						
Rechargeable Transmitter	No			No	Yes (ACT-202T)			
Frequency Range	480~934 MHz (country dependent)							
Bandwidth	24 MHz							
Audio Player								
Built-in USB Port	Yes			No	Yes			
Digital Audio Player	Built-in USB Player Recorder			No	Built-in USB Player SD card reader			

<sup>\*</sup>Crowd coverage can be increased substantially with the use of an identical wireless PA system or a passive extension speaker.

All units run on battery & mains power and are supplied with an AC power cord

All models incorporate 'one-touch' SCAN & SYNC (ACT)

Max wireless microphone operating range is 50-100 meters (165-330 feet)

Specifications & design subject to change without notice MA 014/09