

MM-202B Gooseneck Microphone

Key Features

- Ultra slim profile design for podiums, pulpit and lectern applications.
- Proprietary microphone mount design allows 110° up/down and 300° left/right angle adjustments.
- Shock isolation mount design minimizes handling and vibration noise.
- Multi-layered microphone grill minimizes pop noise.
- Can be connected to MJ-53 Condenser Microphone Adaptor and provides with 48V phantom power and used as a desktop gooseneck microphone.
- Unmatched high fidelity sound reproduction.

Related

|         |                                                 |
|---------|-------------------------------------------------|
| ACT-7T  | Bodypack Transmitter                            |
| ACT-30T | Bodypack Transmitter                            |
| ACT-50T | Bodypack Transmitter                            |
| ACT-70T | Wideband Bodypack Transmitter                   |
| ACT-80T | Wideband Digital Miniature Bodypack Transmitter |
| BC-100  | Wireless Boundary Microphone                    |
| MD-101  | Bodypack Transmitter Holder Base                |

Technical Specifications

|                    |                                            |
|--------------------|--------------------------------------------|
| Capsule Module     | 10mmØ Uni-directional condenser microphone |
| Frequency Response | 50Hz~18kHz                                 |
| Sensitivity        | -46dBV± 3dBV/Pa (0dB=1V/Pa)                |
| Maximum SPL        | 142dB (Typical, 1%THD)                     |
| Plug               | TA4F 4-pin Connector                       |
| Length             | 370mm / 14.5"                              |
| Color              | Black                                      |
| Weight             | Approx. 34g / 1.2oz                        |

