

3Play 425 - Tech Specs



Video Inputs	4 simultaneous inputs Any combination of: HD-SDI, HD Component, SD-SDI, SD Component, Composite, or Y/C (BNC)
Video Outputs	2 fully independent, simultaneous playout channels HD-SDI, HD Component, SD-SDI, SD Component, Composite, or Y/C (BNC) HDMI output Dedicated HDMI multi-view output Network output for over-the-network input to TriCaster
Output Modes	A;B; A+B
Video Formats	NTSC: 1080/30p, 1080/24p, 1080/60i, 720/60p, 720/30p, 720/24p, 480/60i Multi-Standard: NTSC-J; PAL 1080/25p, 1080/50i, 720/50p, 720/25p, 576/25i Supports 16:9 and 4:3 aspect ratios
Recording Channels	4
Recording Capacity	More than 30 hours of combined 1080i storage across internal drive and removable drive (15+ hours per drive) MPEG-2 all I-frame
Genlock	Locks to HD or SD analog signals Supports either tri-level or bi-level sync sources
Multi-Viewer	Supported with 2nd display, including HUD
Audio Inputs	4 SDI Embedded 3 x 2 Balanced 1/4" (Mic/Line) 1 x 2 Balanced XLR (Mic/Line)
Audio Outputs	2 SDI Embedded 1 x 2 Balanced XLR 1 x 2 Balanced 1/4"
Audio Processing	Audio is uncompressed and sampled at 96kHz, 32-bit
Time Code	LTC
A/V Standards	HD-SDI video conforms to SMPTE 292M SD video conforms to SMPTE 259M and ITU-R BT.656 Analog audio levels conform to SMPTE RP-155
Controller	Dedicated controller with T-bar, jog wheel, speed presets, and clip transport
Dimensions	19 x 3.5 x 22.5 (in) 48.3 x 8.9 x 57.2 (cm)
Weight	28 lbs (12.7 kg)