

CPA-120X



CPA-120X.jpg



Small central unit, 180/120 W, 3 RU

Rating: Not Rated Yet

Price:

[Question on item?](#)

Description The new PA centers CPA-120X/240X features 4 switchable 100 V or 70 V speaker lines. The amplifier power amounts 120W/240W. Further features, the external controllable chime, 2 different types of siren, the insertable phantom power as well as an integrated priority function. The device is in the best way suitable for professional application.

Features

- The inputs 1 and 2 are switchable from Mic. to LINE. Both XLR and jack plug (6.3 mm) can be used.
- The inputs 3 - 5 can process both Mic. and LINE signals (XLR = Mic; jack = LINE).
- All Mic/Line inputs are electronically balanced, whereby priority and phantom voltage can be assigned to inputs 1 and 2.
- The amplifier can be operated with 230 V AC or with 24 V DC.
- Additionally to the 4 lines, one 100 V-, one 70 V- and one 8 ohms output are available as unswitched speaker outputs.
- For cascading with further amplifiers as well as for feeding in external tone sources, an AMP-IN and a PRE-OUT are featured.
- An additional Tel-In enables feeding in line signals with priority.
- The 2-tone chime is remote-controlled and can be released e.g. by a school clock or a substation.
- This model offers the option to insert a sound source module into the unit.