HAND-HELD MICROPHONES



Dynamic microphone

Dynamic handheld microphone with cardioid characteristic in the best quality. The low-feedback microphone with built-in wind and pop protection offers a high level of user comfort.

A low-noise on/off switch is integrated into the handle.



Technical data DM-2	02 X
frequency range	120 – 18,000 Hz
directional characteristics	kidney
nominal impedance	600 ohms
sensitivity	-53 dB, ±3 dB
dimensions and weight	Ø 49mm x 180mm (L); approx. 300 g
Switch	ON / OFF with locking screw
Accessories / Scope of delivery	1 connection cable 4 m

Dynamic microphone, with XLR connector symm. DM-202X

Dynamic microphone

Dynamic handheld microphone with cardioid characteristic in the best quality. The low-feedback microphone with built-in wind and pop protection offers a high level of user comfort.

A low-noise on/off switch is integrated into the handle.



Dynamic microphone, with jack plug unbalanced. DM-202K

Electret shotgun microphone (with phantom power 9-52V DC)





Description

The ECM-400 is a shotgun microphone with a lobe pattern and very good directional properties.

Thanks to the optimized frequency response, this microphone achieves a high level of consonant intelligibility and offers ideal conditions for universal use in order to amplify even more distant sound sources with high quality.

A windscreen and a microphone holder are included.

frequency range	30 – 20,000 Hz
directional characteristics	club (shotgun)
nominal impedance	150 ohms
Max. Input Level	130 dB SPL, 1 kHz at 1% THD
dynamics	110 dB, 1 kHz at Max. SPL; S/N ratio 74dB, 1kHz
power supply	Phantom Power 9-52V DC, 2 mA typical
dimensions and weight	Ø 21 mm x 32.5 mm, approx. 200 g
Switch	Bass - Roll-Off switch or Flat
Accessories / Scone of delivery	1 windscreen, 1 microphone holder

Technical data ECM-400

Electret shotgun microphone

(with phantom power)