HAND CALL







The manual call point HMA-001W (white) is specially designed for use in

With the inscription "House alarm" (replaceable) it can be connected directly

to the trigger contacts of an electro-acoustic emergency warning system.

The manual call points are installed in a robust aluminium housing, which, in comparison to plastic housings, is resistant to the environment and can be used for years.

 The pivoting door with an opening angle of 180° has a replaceable glass pane.

- If the detector is triggered, the integrated blocking nose closing the door.
- All manual call points can also be combined with the AAS-200A, DMM-618B or the VARES series systems.
- Replacement glass panes and replacement keys are available as optional nal accessories available.

Technical data HMH-001B HMA-001G HMA-001Y HMA-001O HMA-001W

Housing aluminum die-casting

contacts 1 x changeover contact 48 VAC/DC 1 A
operating temperature -20 to +60 °C
protection class IP43 (according to DIN EN 60 529)

Weight 400 g

lettering house alarm school shooting slarm sch

model names

NGRS systems.

Hand -held alarm »Amokalarm«, green	.HMA-001G
Hand- held alarm »Amokalarm«, yellow	HMA-001Y
Manual alarm "Amokalarm", orange HMA-0	010
Manual call point »Emergency«, white	HMA-001W
according to VDE 0827 for NRGS (emergency and hazard response systems)	

Manual call point »House alarm«, blue	HMH-001B
optional accessories:	
Replacement glass insert	HMG-001
Replacement key. (metal)	. HMS-001