

## Microphone boom (nickel-plated metal tube)



Stable nickel-plated metal tube with black plastic parts. Length: 85 cm, threaded connection  $\frac{1}{4}$ ", weight: 0.9 kg.

**Microphone boom (nickel-plated metal tube) ..... SA-085**

## Microphone floor stand



Sturdy floor stand features anti-vibration design and  $\frac{1}{4}$ " thread. It extends up to 180 cm. The nickel-plated tubes have a handy folding mechanism.

**Floor stand ..... BS-180**

**Floor stand ..... BS-185**  
with boom arm

## Microphone floor stand



Sturdy floor stand with  $\frac{1}{4}$ " thread and nickel-plated tubes. It extends up to 180 cm.

A heavy cast base provides stability and less danger of stumbling.

**Floor stand ..... BS-170**

## Microphone boom (matt black metal tube)



Stable matt black metal tube with black plastic parts. Length: 85 cm, threaded connection  $\frac{1}{4}$ ", weight: 0.9 kg.

**Microphone boom (matt black metal tube) ..... SA-090**

## Microphone floor stand

with new mechanism for vertical adjustment



Sturdy and lightweight anti-vibration aluminium stand (black), with new clamping mechanism which provides very easy and silent vertical adjustment. It extends to 170 cm and has a  $\frac{1}{4}$ " thread.

**Floor stand ..... BS-190**

**Floor stand ..... BS-195**  
with boom arm

## Desktop microphone stand with boom arm



Sturdy desktop stand with boom arm that extends up to 40 cm. Threaded connections:  $\frac{1}{4}$ " and  $\frac{1}{8}$ ".

**Desktop stand ..... TS-060**

## Desktop microphone stand



Handy and lightweight, but stable tripod stand with  $\frac{1}{4}$ " and  $\frac{1}{8}$ " threads.

**Desktop stand ..... TS-010**



SH-330 X

SH-300

SH-150

Gooseneck (13", black), approx. 33 cm long, with male XLR and female XLR.

**Gooseneck ..... SH-330 X**

Rugged gooseneck, approx. 30 cm long, with adapter for  $\frac{1}{4}$ " and  $\frac{1}{8}$ " threaded connection.

**Gooseneck ..... SH-300**

Rugged gooseneck, approx. 15 cm long, with adapter for  $\frac{1}{4}$ " and  $\frac{1}{8}$ " threaded connection.

**Gooseneck ..... SH-150**

## Gooseneck flange



Chrome-plated flange plate ( $\varnothing$  approx. 45 mm) for mounting microphone goosenecks.

Flange plate has  $\frac{1}{4}$ " and  $\frac{1}{8}$ " threaded adapter.

**Gooseneck flange .. SF-100**

## Desktop microphone stand



Sturdy desktop stand which extends up to 40 cm, with heavy cast-iron base and  $\frac{1}{4}$ " and  $\frac{1}{8}$ " threaded connections.

**Desktop stand ..... TS-040**

## Microphone Socket

flush mounting

Picture shows MD-055 UX



Socket with white plastic cover for flush mounting in 55 mm boxes. Can be combined with products of the Jaeger-Busch design program.

**Microphone Socket** ..... **MD-055 UD**  
with DIN socket

**Microphone Socket** ..... **MD-055 UX**  
with XLR socket

## Microphone Socket

surface mounting, inc. surface mounting box

Picture shows MD-055 AX



Socket with white plastic cover for surface mounting. Inc. plastic surface mounting box. Colour: alpine white. Dimensions 85 x 85 x 45 mm. Can be combined with products of the Jaeger-Busch design program.

**Microphone Socket** ..... **MD-055 AD**  
with DIN socket

**Microphone Socket** ..... **MD-055 AX**  
with XLR socket

## Microphone Socket

Floor socket



Aluminium die cast socket with cover for floor and wall mounting. Colour: hammered grey. Dimensions: 85 x 85 x 65 mm.

**Microphone Socket** ..... **MD-100 FD**  
with DIN socket

**Microphone Socket** ..... **MD-100 FX**  
with XLR socket

## Microphone Clip (universal)



This microphone clip fits all common microphone types, also microphones with cone shaped handles. Threaded connection:  $\frac{3}{8}$ " and  $\frac{5}{8}$ ".

**Microphone Clip** ..... **MH-101**

## Microphone Holder (antishock)



This newly developed micro-phone holder dampens vibrations by means of its special rubber suspension. Threaded connection:  $\frac{3}{8}$ " and  $\frac{5}{8}$ ".

**Microphone Holder** ..... **MH-200**

## Twin Microphone Mount



This Twin-Microphone Mount is designed for the mounting of 2 or 3 mics. It is equipped with two threaded connections  $\frac{3}{8}$ " and can be combined with any floor stand of our product range. The distance between the two connections are 21 cm.

**Microphone Mount** ..... **ZS-200**

## Floor Tank-XLR



This floor tank is made out of a 3 mm steel plate (black burned-in varnish). It is assembled with 4 XLR-jacks. It has a hinged lid and is therefore perfectly suitable for floor installations.

The minimum installation depth is 70 mm and the outside dimensions are 200 x 200 mm. The attachment hole space is 102 x 140 mm. The 4 compatible attachment screws (M5 x 40 mm) are included in the scope of delivery.

**Floor Tank XLR** ..... **WBT-400 X**  
with 4 XLR-plugs

## Floor Tank-Speaker



This floor tank is made out of a 3 mm steel plate (black burned-in varnish). It is assembled with 4 Speaker-jacks. It has a hinged lid and is therefore perfectly suitable for floor installations.

The minimum installation depth is 70 mm and the outside dimensions are 200 x 200 mm. The attachment hole space is 102 x 140 mm. The 4 compatible attachment screws (M5 x 40 mm) are included in the scope of delivery.

**Floor Tank Speaker** ..... **WBT-400 S**  
with 4 Speaker-plugs