## SONY







Sony has introduced two optional interface modules that further extend the Anycast Station system's wide-ranging capabilities: the BKAW-560 HD Analogue Component I/O Module and the BKAW-590 HD-SDI I/O Module. Users can now migrate from analogue to digital or SDI to HD simply by swapping the modular BKAW interface cards.

## **Technical Specifications**

**SDI IN** 

SDI OUT\*

- BNC Type x 2
- Video: 800 mVp-p (75 ohms), SMPTE 292M 1080 50i / 59.94i , 720 50P / 59.94P
- Audio sampling rate: 20bit, 48kHz, 2 channels (channel 1 and 2, or 3 and 4)/ SMPTE 299M
- BNC Type x 1
- Video: 800 mVp-p (75 ohms), SMPTE 292M 1080 50i / 59.94i , 720 50P / 59.94P
- Audio sampling rate: 20bit, 48kHz, 2 channels (channel 1 and 2)/ SMPTE 299M

## **Compatible Products**

**Anycast Station** 

AWS The A

AWS-G500

The Anycast Station is a unique portable solution incorporating video switching and audio mixing with high quality LCD

display for producing live broadcast events.

<sup>\*</sup> The output is active when 16:9 HD mode is selected for Program Output Aspect Ratio.