

| |
|------------------|
| CA-D50//U |
| Camera Adaptor |



Camera Adaptor for use with the CCU-D50/D50P
Camera Control Unit. Dockable to Sony DXC cameras

that employ the 76-pin digital connector Interfaces
with 26-pin equipped Sony portable VTRs

Technical Specifications

| | |
|------------------------|---|
| Power requirements: | DC 12 V |
| Power consumption: | Approx. 3.8 W |
| Operating temperature: | -10°C to 45°C (14°F to 113°F) |
| Storage temperature: | -20°C to 55°C (-4°F to 131°F) |
| Dimensions: | 113 (W) 3 183 (H) 3 168 (D) mm (7 1/4 3 4 1/2 3 6 5/8 inches) |
| Mass: | 1.1 kg (2 lb 7 oz) |

| Input/Output connectors | |
|--------------------------|-----------------------------------|
| Camera interface: | Pro 76-pin DIGITAL (1) |
| CCU/VTR/CMA: | Sony Z-type 26-pin (1) |
| SDI output: | BNC (1), 270 Mb/s, 0.8 Vp-p, 75 ½ |
| Genlock/Prompter output: | BNC (1), 1.0 Vp-p, 75 ½ |
| Earphone: | Mini jack |
| Intercom: | Mini intercom jack |
| DC input: | XLR 4-pin (1), 10.5 to 17.0 V |