

HDVF-L750

Full HD 7-inch LCD viewfinder



Overview

Large Full HD 1920 x 1080 7-inch LCD panel ideal for 4K live production in operation with Sony studio cameras, XDCAM camcorders, F65 and PMW-F55

The HDVF-L750 Full HD 7-inch LCD viewfinder is usable with the whole range of Sony studio cameras, XDCAM camcorders (with supplied VF cable and V-shoe adaptor), F65 and PMW series camcorders such as the PMW-F55 and PMW-F5 in 4K and HD live production configurations. The 1920 x 1080 LCD panel allows for more precise focusing, with a very high 1000:1 contrast ratio and WFM (waveform monitor) function for very precise exposure control. A 3G-SDI input connector adds flexibility for viewing external sources apart from the camera signal, while two assignable switches on the bezel allow for bespoke setups. The viewfinder also has a simple hood to help minimise glare.

- **Full HD 1920 x 1080 7-inch LCD panel ideal for 4K and HD live production**

Easier and more precise focusing, especially in 4K applications in operation with F65 and PMW-F55 cameras.

- **1000: 1 high contrast ratio**

Better picture viewing in outside broadcast live applications.

- **WFM (waveform monitor) function**

All-in-one picture control monitoring for very precise exposure control.

- **External 3G-SDI input connector**

Allows you to check external video sources in the field, including third party equipment.

Features

- **Full HD 1920 x 1080 7-inch LCD panel with high contrast ratio**

The precision 1920 x 1080 pixels LCD panel delivers stunning Full HD quality for easier and more precise focusing, especially in 4K applications in operation with F65 and PMW-F55 cameras. The viewfinder also attaches to all Sony studio cameras and XDCAM camcorders (with supplied VF cable and V-shoe adaptor).

- **High contrast ratio**

The very high 1000:1 contrast ratio provides better picture viewing in outside broadcast live applications.

- **WFM (waveform monitor) function**

The WFM function provides all-in-one picture control monitoring for very precise exposure control and optimal focus adjustment.

- **External 3G-SDI input connector**

The 3G-SDI input allows you to monitor SDI external signals up to 3G-SDI. You can check external video sources in the field, including third party equipment, and have an additional video return in addition to the camera.

- **Assignable switches on bezel**

The HDVF-L750 offers a two assignable switches on the bezel for bespoke setups.

- **Simple hood, plus HDVF cable**

The viewfinder is supplied with a simple hood, as well as a HDVF cable.

Compatible Products

4K and HD System Cameras



HDC-1700

Multi format HD portable system camera



HDC-2500

3G double-speed multi format HD system camera



HXC-FB75H

Affordable three 2/3-inch Exmor CMOS sensors SD / HD Studio Camera



HXC-FB75KC

Affordable three 2/3-inch Exmor CMOS sensors SD / HD Studio Camera with viewfinder, monoral microphone and 20x zoom lens

XDCAM



PXW-X320

Three 1/2-inch type Exmor CMOS sensors XDCAM camcorder with 16x zoom HD lens recording Full HD XAVC 100 Mbps, with wireless options



PXW-X400

Three 2/3-inch type Exmor CMOS sensors XDCAM weight-balanced advanced shoulder camcorder with improved network connectivity and low power consumption



PXW-X500

Three 2/3-inch type PowerHAD FX Full HD CCD sensors XDCAM camcorder with multi-format recordings including XAVC