



Telescript teleprompters



FPS-120

**12" Full-Color LCD
Prompting System**

*A Revolution in
Intelligent Design*



Telescript's FPS-120

Works the way you want.

From news room to board room, from convention stage to sound stage - the award-winning **FPS-120 Prompting System** delivers portability and flexibility in any environment you demand.



Portability

Never before has it been so easy to transport an entire prompting system. Telescript's custom-designed ATA-rated travel cases (*at right*) and **QuickMount** easy mounting system (*below*) save you time and effort.



Simplicity

Telescript's exclusive **QuickMount** technology brings a radical change to teleprompter mounting. The system comes apart in essentially two pieces, making setup and transport effortless.



Flexibility

The **FPS-120** offers many options to extend its use, such as the **DirectView** mounting system (*at right*) that puts the prompter right above the camera lens; DV and small format riser mounts, and battery pack mounts (*top right*).



Technical Specifications

Display

Size:	12" (30.48 cm)
Brightness:	300 nits (Standard) 900 nits (Hi-bright)
Resolution:	1024 x 768 XGA max
Video Input:	NTSC/PAL Composite video 1V p-p 75ohm, XGA
Video Output:	Composite video 1V p-p 75ohm (passive)
Video Conn.:	2 BNC (1 in /1 out), 15 pin VGA (1 in), 4 pin S-Video
Power Input:	12 V DC via 4 pin XLR
Power Supply:	External 90-240V 50/60hz AC
Power Consum.:	14 W max

System

Total System Wt.:	13 lbs (5.9 kg)
Usable Distance:	2-30' (.61- 9.14m)
Material:	Aircraft aluminum
Mounted Dim.:	13.5"W x 31.5"D x 11.75" to 18"H (34.3cmW x 80cmDx 29.8 to 45.7cmH)
Display Dim.:	13.5W x 10.75"D x 2"H (34.3cmW x 27.3cmD x 5.1cmH)
Beamsplitter Dim.:	12.75" x 12.75" (32.5cm x 32.5cm)
Beamsplitter Reflective/Transmissive%:	30/70
Options:	DirectView Mount, Riser (for DV cams), Battery Adapter Plate, 5 lb Counter Balance Weight, Custom Cases