

C-Box (Converter, Gold Mount)



(//Cdn3.volusion.com/akmsw.skkga/v/vspfiles/photos

/176400-2.jpg?1466066349)

(//Cdn3.volusion.com/akmsw.skkga/v/vspfiles/photos/176400-2.jpg?1466066349)

C-Box (Converter, Gold Mount) accepts HDMI and 3G HD-SDI input, selectable via a switch on the operator's side, and simultaneously outputs three channels of HD-SDI and two of HDMI. The device draws power internally from the male Gold Mount plate attached and passes power through to the camera via the female Gold Mount plate on the other side. The male Gold Mount plate has an additional D-Tap output for accessory power. Each HD-SDI output is independently reclocked and carries the same strength as the original signal. LED indicators are located on the operator's side to show status of power and signal. 5V Mini USB port on operator's side for powering wireless transmitters like Paralinx, IDX Cam-Wave, etc.

This version attaches between any Anton Bauer QRC size Gold Mount plate and Gold Mount battery. For example, the C-Box (Converter, Gold Mount) can fit between an Anton Bauer Dionic HC battery and the **QB Anton Bauer (QRC-EPIC)** (</Product-p/149500.html>).

SPECIFICATIONS:

Weight: 635g (1.4 lbs)

Dimensions: 127 x 76 x 178 mm (5.0 x 3.0 x 7.0 in)
