

# D-Box (Alexa Mini, Gold Mount)

---



(//Cdn3.volusion.com

/akmsw.skkg/v/vspfiles/photos/209100-2.jpg?1479822951)

(//Cdn3.volusion.com/akmsw.skkg/v/vspfiles/photos/209100-2.jpg?1479822951)



D-Box (Alexa Mini, Gold Mount) is a custom version of our popular D-Box that adds power distribution, standardized remote start/stop, and hot swap abilities for the ARRI Alexa Mini. Two 16 inch (40cm) cables exit the power plate with one going to the 8pin LEMO compatible power plug and the other going to the 7pin EXT port.

The bottom of the D-Box has (3) 1/4-20 holes which can attach directly to our **Rod Clamp (15mm LW)** ([Http://akmsw.skkgg.servertrust.com/product-p/150200.html](http://akmsw.skkgg.servertrust.com/product-p/150200.html)), **Rod Clamp (15mm Studio)** ([Http://akmsw.skkgg.servertrust.com/product-p/150300.html](http://akmsw.skkgg.servertrust.com/product-p/150300.html)), and **Rod Clamp (19mm)** ([Http://akmsw.skkgg.servertrust.com/product-p/150400.html](http://akmsw.skkgg.servertrust.com/product-p/150400.html)). For an adjustable mount system, use the **Battery Slide** ([Http://akmsw.skkgg.servertrust.com/product-p/156600.html](http://akmsw.skkgg.servertrust.com/product-p/156600.html)) or **Recorder Slide** ([Http://akmsw.skkgg.servertrust.com/product-p/191100.html](http://akmsw.skkgg.servertrust.com/product-p/191100.html)) paired with the same Rod Clamps listed above.

This product will attach to the ARRI BAP-1 and instructions on how to do this are included in the box.

## OVERVIEW:

Authentic Anton Bauer plate provides 1x D-Tap (unregulated) and is hard wired to the D-Box.

## D-BOX SLOTS INCLUDED:

1. 7 pin LEMO compatible - EXT Port

- Replica of connector on rear of camera
- Maintains functionality of external communication, R/S, and power
- Note this slot is **NOT** swappable

2. 2 pin LEMO compatible - 12V Unregulated

- ARRI standard wiring
- This slot can be swapped for Hirose, 4pin LEMO, or D-Tap (note that only 1x D-Tap can occupy slot 2 or 3)

3. 2 pin LEMO compatible - 12V Unregulated

- ARRI standard wiring
- This slot can be swapped for Hirose, 4pin LEMO, or D-Tap (note that only 1x D-Tap can occupy slot 2 or 3)

4. 3 pin Fischer - 24V Regulated

- Regulator built in to convert battery voltage to 24V
- Maximum 3A shared between slot 4/5
- Note this slot is **NOT** swappable

5. 3 pin Fischer - 24V Regulated

- Regulator built in to convert battery voltage to 24V
- Maximum 3A shared between slot 4/5
- Note this slot is **NOT** swappable

#### 6. 4 pin Mini XLR - 12V Input

- Hot swappable power input with included 8 inch pigtail cable for standard 4 pin XLR (12V nominal)
- Capable of providing power to accessories and camera without brick battery attached
- Note this slot is **NOT** swappable

Connectors used in this assembly are not manufactured by LEMO but are made to the same specifications and are LEMO compatible.

#### **SPECIFICATIONS:**

Weight: 534 grams (1.18 lbs)

Dimensions: 90 x 146 x 43mm (3.5 x 5.7 x 1.7 inches)

---